

SMD Chip LEDs

Part No.	Emitting light	Chip material	Len's type	Iv (mcd)	d (nm) (Typical)	Typical Vf(v)	View Angle (2θ1/2)
SM-150RC	Red	AllnGaP	Water clear	5~20	630	1.9	120~160°
SM-150URC	Red	AllnGaP	Water clear	40~100	630	1.9	120~160°
SM-150YC	Yellow	AllnGaP	Water clear	5~20	590	2	120~160°
SM-150UYC	Yellow	AllnGaP	Water clear	40~100	590	2	120~160°
SM-150GC	Green	GaP	Water clear	3~8	565	2.1	120~160°
SM-150UGC	Green	InGaN	Water clear	150~300	525	3.5	120~160°
SM-150UBC	Blue	GaN	Water clear	150~300	470	3.5	120~160°
SM-155Y/GC	Yellow/Green	GaAsP/GaP	Water clear	16-十二月	589/568	2.1	120~160°
SL-PCLL-R	Red	GaAsP	Water clear	23	635		
SL-PCLL-R/G	Red/Green	GaAsP/GaP	Water clear	23/20	635/565		
SL-PCLL-SR	Super Red	GaAlAs	Water clear	140	660		
SL-PCLL-SR/G	Red/Green	GaP	Water clear	70	570		
Test Condition: If = 20mA							