

SR25-LANDSCAPE(LS25) EXTERIOR LUMINAIRE

0-10V DIMMING | SMART LIGHTING COMPATIBLE | EXTERNAL DRIVER





PRODUCT NAME	LANDSCAPE25
INPUT	700mA or 12VDC
POWER FACTOR	>0.9
POWER CONSUMPTION	2.2W or 6.5W
DIMMING	0-10V dimming for 700mA fixtures
MATERIAL	Anodized extruded aluminum, glass lens
WEIGHT	0.1 lb (0.05 kg)
LENGTH	4"
MOUNTING	Swivel Mounted
LIFETIME	> 60,000 hrs
WARRANTY	Five year limited warranty
OPTICS	Milled aluminum primary optic, clear glass lens aluminum reflector, optional translucent diffuser
OPERATING RANGE	-30°C to 40°C
BEAM ANGLE	Standard 90°, Diffused 110°




WET LOCATION [IP66]

Patented Fixture



LS25M1X3-35



LS25M1X3-35

PRODUCT & LED MODULE SIZE	INPUT CURRENT	POWER CONSUMED	LUMEN OUTPUT	FIXTURE EFFICACY
LS25 M1X1	700 mA	2.2 W	231 LM	107 LM/W
LS25 M1X3	700 mA	6.5 W	693 LM	107 LM/W

Specialty designs with different chips per module available upon request

CCT	2,700K	3,500K	4,100K	5,500K
LIGHT OUTPUT CONVERSION	.95	1.0	1.05	1.16
CRI	80	80	80	75

PRODUCT	LED MODULE SIZE	CURRENT/VOLTAGE	HOUSING COLOR	COLOR TEMPERATURE
LS25		-	-	-
LS25	M1X1	1 MODULE 1 CHIPS	SV SILVER	55 5500K
	M1X3	1 MODULE 3 CHIPS	BK BLACK	41 4100K
			BR BROWN	35 3500K
				27 2700K
			27/55 CCT TUNING	
			RGB RGB	

