



SUNSTRIP30 (ST30) COVE LUMINAIRE

0-10V DIMMING | SMART LIGHTING COMPATIBLE | EXTERNAL DRIVER




PRODUCT NAME	SUNSTRIP30
INPUT	700mA or 1400mA
POWER FACTOR	>0.9
POWER CONSUMPTION	30W or 60W
DIMMING	0-10V dimming
MATERIAL	Anodized extruded aluminum, glass lens
WEIGHT	1.2 lbs (.55kg) or 2.4 lbs (1.1kg)
LENGTH	48" or 96"
MOUNTING	Recessed, Surface mounted, Swivel, Suspended
LIFETIME	> 60,000 hrs
WARRANTY	Five year warranty
OPTICS	Optional translucent diffuser
OPERATING RANGE	-30°C to 40°C
BEAM ANGLE	Standard 90° Diffused 170°




DAMP LOCATION [IP64]

Higher CRI (85, 90, or 95) are available upon request.



ST30Y48P4X15-D-50



ST30Y48P4X15-DD-50

PRODUCT & LED MODULE SIZE	INPUT CURRENT	POWER CONSUMED	LUMEN OUTPUT	FIXTURE EFFICACY
ST30Y96P8X15	1400 mA	60 W	9,400 LM	156 LM/W
ST30Y48P4X15	700 mA	30 W	4,700 LM	156 LM/W
ST30Y24P2X15	350 mA	15 W	2,850 LM	156 LM/W
CCT	2,700K	4,100K	5,000K	
LIGHT OUTPUT CONVERSION	.87	0.95	1	
CRI	80	80	80	

PRODUCT	LENGTH	LED MODULE SIZE		CURRENT	
ST30					
ST30	Y24 24 INCHES	P2X15	2 MODULES WITH 15 CHIPS EACH	0350	mA
	Y48 48 INCHES	P4X15	4 MODULES WITH 15 CHIPS EACH	0700	mA
	Y96 96 INCHES	P8X15	8 MODULES WITH 15 CHIPS EACH	1400	mA
DIFFUSED	HOUSING COLOR	COLOR TEMPERATURE		MOUNTING BRACKET STYLE	
-	-	-	-	-	-
D	DIFFUSED SV SILVER	50	5000K	RCM	RECESSED CEILING MOUNT TDS-WW TDS WALL WASHER
DD	DOME DIFFUSED BK BLACK	41	4100K	SM	SURFACE MOUNT RCS-WW RCS WALL WASHER
ND	NON-DIFFUSED	27	2700K	TDS	TRADITIONAL SUSPENDED BASE
		30	3000K	RCS	RECESSED SUSPENDED BASE
				WM	WALL MOUNT
				SWV	SWIVEL MOUNT

