

## DESCRIPTION:

Patent pending luminaire, SunStar25-Pendant, is one of the brightest pendants on the market at its extremely small size (1" Ø). Energy efficient, innovative, and lightweight the PD25M1X3 is a designer friendly pendant series with brightness levels up to a traditional 50W equivalent. Pendant25 comes in a standard version with a 90° beam. With super bright energy efficient LEDs, the Pendant25's slim profile, rugged construction, and multiple finishes make this 124 lm/watt (PD25M1X3) pendant the right choice for illuminating any installation where the best illumination, endless design options, and energy savings are desired.

## SPECIFICATIONS:

### LUMINAIRE:

Total luminaire length 5" to 48"  
1" diameter housing with three available mounting options (Traditional: 2.5" Ø by ¾" H Silver or Recessed: 1.5" Ø Flush Mount White/Silver). Includes one upgradable module.

### CONSTRUCTION:

Extruded aluminum housing has a diameter of 1". Metal mounting bracket is mechanically fit to ceiling with no exposed fasteners.

### MODULE:

One three chip LED module utilizing Sunlite patented application specific technology with four standard color temperature options (2700K, 3500K, 4100K, and 5500K).

### CONTROLS:

0-10V Dimming when utilizing suggested dimming AC-DC driver down to 10%. Smart lighting compatible.

### OPTICS:

Optical system consists of milled aluminum primary optic, clear glass lens, and aluminum reflector.

### FINISH:

Standard finish for housing is anodized aluminum. Consult factory for custom colors.

### ENVIRONMENT:

Damp location rated. Fixture operating temperature -30°C to 40°C.

### WARRANTY:

Five-year warranty for fixture and driver. Terms and conditions apply.

### ELECTRICAL:

Pendant25 setup consists of multiple fixtures and a [0-10V dimming] AC-DC driver rated. Fixture input wattage is 6.5W for 693 delivered-lumen package per 3500K fixture. PD25 contains an LED shunt protection device.

Must Specify driver. Specify 110V to 277V to driver. Wire lights in series with CL2/18-2. For special circuiting or wire gauge, consult factory.

### LIFETIME:

Designed and built to last over 60,000 hours.

### VALIDATION:

UL/cUL listed.

### SHIPPING:

Approximate net shipping weight varies by length 0.1 lbs (0.05 kg) for 5" to 1.1 lbs (0.49 kg) for 48".



PROJECT:

PRODUCT:

LOCATION:

CONTACT:




## SUNSTAR25 PENDANT LIGHT PD25M1X3

## SOLID STATE LED

### USE:

## TRADITIONAL 50W EQUIVALENT

## DIMENSIONS:



### CONTACT:

4811 Quail Crest Place  
Lawrence, KS 66049  
www.sunlitest.com  
T:785.856.0219

### CERTIFICATION:

UL and cUL  
Damp Location Listed  
IP64 Rated

### ENERGY:

>0.9 Power Factor  
700mA / ~10VDC  
-30° C to 40°C  
6.5W

### SHIPPING:

Approx. Net Weight  
Varies By Length  
0.1 lbs (0.05 kg) for 5"  
1.1 lbs (0.49 kg) for 48"

# CATALOG NUMBER:

EXAMPLE PRODUCT CODE: PD25M1X3-0700-SV-35-05-TD


-  -  -  -  -  -

PRODUCT	LED MODULE SIZE		CURRENT	HOUSING COLOR		COLOR TEMPERATURE		HOUSING LENGTH		BASE STYLE		
PD25	M1X3	1 MODULE 3 CHIPS	0700	mA	SV	SILVER	55	5000K	05	5 INCHES	TD	TRADITIONAL
					BL	BLUE	41	4100K	08	8 INCHES	RC	RECESSED
					BK	BLACK	35	3500K	12	12 INCHES		
					GR	GREEN	27	2700K	CL	CUSTOM LENGTH		
					PR	PURPLE	SR	SOLID RED				
					SG	SOLID GREEN						
					SB	SOLID BLUE						

## RECOMMENDED DRIVERS:

### BASIC DRIVERS AND WIRING (UP TO 6 FIXTURES IN A SERIES)

NON-DIMMABLE DRIVERS					
LPLC-18-700		LPC-35-700			
1 OR 2 IN A SERIES		3 TO 5 IN A SERIES			
DIMMABLE DRIVERS					
LUC-010S070DSM	LUC-018S070DSP	EUC-026S070DSC	EUC-042S070DSC	LUC-24S070DSW (NO WIRES)	LUC-42S070DSW (NO WIRES)
1 FIXTURE	2 IN A SERIES	2 OR 3 IN A SERIES	3 TO 5 IN A SERIES	2 OR 3 IN A SERIES	3 TO 5 IN A SERIES
LPF25D-36 (DIM TO OFF)					
3 IN A SERIES					



CALL FOR SPECIALTY DRIVER OPTIONS

## LUMEN OUTPUT:


COLOR TEMPERATURE	WATTAGE	LUMEN	CRI
2700K	6.5	659	80
3500K	6.5	693	80
4100K	6.5	728	80
5500K	6.5	804	75

## WORKPLANE FOOT CANDLE:

DISTANCE FROM WORKPLANE	HALF VALUE COVERAGE (FT)	LIGHT LEVEL (FC)
1.5	2.6	216
2	3.5	121
3.5	6	40

FC = FOOT CANDLE


## PHOTOMETRICS:



PD25M1X1-35

PD25M1X1-35

## DUV RANGE:



## TYPICAL MOUNTING CONFIGURATIONS:

Standard Cable Length is 3'. Consult factory for a different length.

