

DESCRIPTION:

Unique luminaire, SunStrip30-N, is a revolutionary energy saving linear fixture with an efficacy of 157 lm/watt (ST30Y48P4X15N). This ST30N fixture has an extremely sleek profile (1-1/4" W X 1-1/4" H), only weighs 1.3 lbs, and is UL/cUL listed for damp (IP64) locations. The ST30Y48P4X15N luminaire comes standard with a diffuser which provides a 170° beam angle, optionally without a diffuser which provides a 90° beam angle. The modular nature of the ST30N product line makes it scalable not only in linear footage and lumen output, but also in the price structure: providing flexibility in all design aspects of a project which allows for the perfect lighting scheme to be achieved. With super bright energy efficient LEDs, the SunStrip30's sleek profile, rugged construction, multiple mounting options, and multiple finishes make this ST30Y48P4X15N linear light the right choice for illuminating any installation where the best illumination, sleek integrated design, and energy savings are desired.

SPECIFICATIONS:

LUMINAIRE:

Total luminaire length 48".
31mm X 31mm profile with five available mounting options.

CONSTRUCTION:

Extruded anodized aluminum housing has a 31mm X 31mm profile. Metal mounting brackets are mechanically fit to fixture.

MODULE:

Four LED modules with fifteen chips utilizing Sunlite proprietary application specific technology with five available color temperature options (2700K, 3000K, 3500K, 4100K, and 5000K).

CONTROLS:

0-10V Dimming when utilizing suggested dimming AC-DC driver down to 10%. Smart lighting compatible.

OPTICS:

Optical system consists of high performance diffuser with transmission of over 90%, which hides the LED source and provides excellent glare control.

FINISH:

Standard finish for housing is anodized aluminum. Consult factory for custom colors.

ENVIRONMENT:

Damp location rated. Fixture operating temperature -30°C to 40°C.

WARRANTY:

Five-year warranty for fixture and driver. Terms and conditions apply.

ELECTRICAL:

SunStrip30 setup consists of multiple fixtures and [0-10V dimming] AC-DC driver. Fixture input wattage is 30W for 4700 delivered-lumen package per 5000K fixture.

Specify 110V to 277V to driver. Wire lights with 18AWG CL2 wire. For special circuiting or wire gauge, consult factory.

LIFETIME:

Designed and built to last over 60,000 hours.

VALIDATION:

UL/cUL listed.

SHIPPING:

Approximate net shipping weight is 1.3 lb (0.57 kg).



PROJECT:

PRODUCT:

LOCATION:

CONTACT:



SUNSTRIP30

STRIP LIGHT



ST30Y48P4X15N

SOLID STATE LED

USE:

LINEAR LIGHT

DIMENSIONS:



CONTACT:

4811 Quail Crest Place
Lawrence, KS 66049
www.sunlitest.com
T:785.856.0219

CERTIFICATION:

UL and cUL
Damp Location Listed
IP64 Rated

ENERGY:

>0.9 Power Factor
700mA / ~ 48VDC
-30° C to 40°C
30W

SHIPPING:

Approx. Net Weight
1.3 lbs (0.57 kgs)

CATALOG NUMBER:

EXAMPLE PRODUCT CODE: ST30Y48P4X15N-D-0700-SV-50-MPB


[]		[]		[]		[]		
PRODUCT	LENGTH	LED MODULE SIZE		SECONDARY LENS				
ST30	Y48 48 INCHES	P4X15N	4 MODULES WITH 15 CHIPS		D	DIFFUSED LENS		
					CL	CLEAR LENS		

CURRENT	HOUSING COLOR	COLOR TEMPERATURE		MOUNTING BRACKET STYLE				
0700 MA	SV SILVER	50	5000K		MPB	METAL PIVOT BRACKET		
	BK BLACK	41	4100K		RCS	RECESSED SUSPENDED BASE		
	CC CUSTOM COLOR	35	3500K		TDS	TRADITIONAL SUSPENDED BASE		
		30	3000K					
		27	2700K					

RECOMMENDED DRIVERS:

BASIC DRIVERS AND WIRING

NON-DIMMABLE DRIVERS					
LPC-35-700					
1 FIXTURE					
DIMMABLE DRIVERS					
EUC-042S070DSC	LUC-042S070DSW (NO WIRES)				
1 FIXTURE	1 FIXTURE				



CALL FOR DRIVER OPTIONS FOR MULTIPLE FIXTURES

LUMEN OUTPUT:

COLOR TEMPERATURE	WATTAGE	LUMEN	CRI*
2700K	30	4089	80
3000K	30	4170	80
3500K	30	4290	80
4100K	30	4465	80
5000K	30	4700	80


* CRI > 90 ARE AVAILABLE UPON REQUEST

WORKPLANE FOOT CANDLE:

DISTANCE FROM WORKPLANE	HALF VALUE COVERAGE (FT)	LIGHT LEVEL (FC)
3	6	231
6	13	58
8	17	33
10	21	21

FC = FOOT CANDEL

PHOTOMETRICS:



ST30Y48P4X15N-D-50

TYPICAL MOUNTING CONFIGURATIONS:

